

# DATACARD® MX6000™ CARD ISSUANCE SYSTEM

## CARD INPUT MODULE

The card input module on the MX6000 system feeds cards reliably into the system. Multiple card input modules can be installed in a system to allow multiple card stocks to be selected within a single card run or to increase capability for large jobs.

- Reliable card picking technology
- Tray capacity of over 500 cards
- Configurable with up to four card input modules
- Selectable card picking from multiple trays

Card Input Module Specifications	
Module Functionality	Feeds the card into the system
Rated Speed	Up to 1,500 CPH
Capacity	1 non-removable tray per module; 550 (0.03 in. thick) non-embossed cards per tray
System Configuration	Up to 4 modules per system
Card Types Supported	ISO/IEC 7810 ID-1 Size; 30 mil ( $\pm 10\%$ ); Alternative card thicknesses can be made available upon request
Card Materials Supported	See system level specifications; no further limitations
Module Dimensions	50.1 in. H x 10.0 in. W x 33.8 in. D (127.3 cm x 25.4 cm x 85.9 cm)
Weight	100.0 lbs (45.4 kg)
Current Draw	0.40 Amps at 230V
Heat Output	Average of 309 BTUs per hour

[www.datacard.com](http://www.datacard.com)

Datacard and MX6000 are registered trademarks, trademarks and/or service marks of DataCard Corporation in the United States and/or other countries.  
©2006-2007 DataCard Corporation. All rights reserved.  
Information subject to change without notice.  
CI7-5257

**Datacard**Group

SECURE ID AND CARD PERSONALIZATION SOLUTIONS